



HME-800
HME-800E

Features

- ✓ **High Performance Network Switching Technology**
- ✓ Complies with IEEE 802.3, IEEE 802.3u, IEEE 802.3X, IEEE 802.1p, IEEE 802.1q, IEEE 802.1d, IEEE 802.1w
- ✓ Provides 8 x 10/100 Mbps Ethernet ports with RJ-45 connector
- ✓ RJ-45 Port support auto MDI/MDI-X crossover
- ✓ Provides broadcast storm protection
- ✓ Redundant X-Ring recovery time < 300 ms on full load
- ✓ Supports Dual Homing – RSTP over X-ring
- ✓ SNMP for network management
- ✓ IGMP snooping for multicast traffic
- ✓ QoS / ToS to increase network packet determinism
- ✓ VLAN for easy network planning
- ✓ Event notification by e-mail, SNMP trap, Syslog & Relay output
- ✓ Online Port Mirroring for online debugging
- ✓ Supports IP security
- ✓ Configurable by WEB browser
- ✓ IntraVUE Network Management software compatible
- ✓ **Robust Industrial Design**
- ✓ Robust Aluminum case complying to IP-31 housing standard
- ✓ Supports operating temperature -10 to 70°C & Extended temperature -40 to 80°C
- ✓ DIN-Rail, Panel mount or desktop installation
- ✓ High level of immunity to electromagnetic interference typically found in industrial plant environments or external curb side enclosures
- ✓ **Reliable Power Design**
- ✓ Wide range redundant power design
- ✓ Equipped with redundant power inputs
- ✓ Supports 12 to 48VDC redundant power with polarity reverse protection
- ✓ Removable terminal block



Overview

The Husky Series HME-800 is a highly reliable and fault-tolerant Industrial 8-port Managed Ethernet Switch. It has 8 10/100TX RJ45 ports that support IEEE 802.3/802.3u/802.3x with 10/100M, full/half duplex, and MDI/MDI-X auto-sensing. With its high performance switching device, HME-800 provides redundant self-recovery mechanism in less than 300ms on full load which allows you to establish a redundant Ethernet network to build a back-up ring topology. With powerful network management functions, HME-800 can be remotely configured by Web browser, managed by SNMP. Event notification can be defined via SNMP trap, Syslog, Relay output or E-mail. Security is enhanced with advanced features like Port based VLAN, Tagged VLAN and IP security. Performance is optimized by Quality of Service and IGMP Snooping/querying. The HME-800 is equipped with a terminal block to provide dual power inputs with reverse polarity protection. Its IP-31 housing protection, wide operating temperature of -10 to 70°C and DIN-Rail mounting is suitable for an industrial environment. The E version extends the temperature rating to -40 to 80°C. The HME-800 is a plug-and-play solution for your Industrial Ethernet applications.

Hardware Specifications

Interface

RJ-45 Ports: 8 10/100Base-TX auto-negotiation speed, Full/Half duplex, auto MDI/MDI-X

LEDs: Per port : Link/Activity (Green), Full duplex/Collision (Green)
Per unit: Power x 3 (Green), Fault (Red), R.M. (Orange)

DIP Switch: X-ring, Master, Port break alarm

Alarm: Relay output for port break and power failure

Power Input: VDC 12-48V
Redundant power with polarity reverse protect function and removable terminal block

Power Protection: ESD (Ethernet)
Power Reverse Polarity

Power Consumption: 5.04 watts

Dimensions: IP-31 standard, 54 mm (W) x 135 mm (H) x 105 mm (D)

Installation: DIN-Rail, panel mounting or desktop

Environmental

Operating Temp: Regular:-10 to 70°C
Extended:-40 to 80°C

Storage Temp: -40 to 85°C (-40 to 185°F)

Operating Humidity: 5% to 90% RH (non-condensing)

Technical Specifications

Standard:

IEEE 802.3 10Base-T Ethernet
IEEE 802.3u 100Base-TX Fast Ethernet
IEEE 802.3x Flow Control and Back-pressure
IEEE 802.1p Class of service
IEEE 802.1Q VLAN
IEEE 802.1D Spanning Tree Protocol (STP)
IEEE 802.1W Rapid Spanning Tree Protocol (RSTP)

Network Media:

10Base-T: 2-pair UTP/STP Cat. 3, 4, 5 cable EIA/TIA-568 100-ohm (100m)
100Base-TX: 2-pair UTP/STP Cat. 5/5e cable EIA/TIA-568 100-ohm (100m)

Protocol Technology: CSMA/CD

Switching Architecture: Store and Forward

Performance

Data Transfer Rate:

14,880 pps for Ethernet port
148,800 pps for Fast Ethernet port

MAC Address: 2K

Memory Buffer: 1Mbytes

Back-plane: 1.6 Gbps

Transfer Packet Throughput: 1.19Mpps @ 64bytes

Regulatory Approvals

EMI: FCC Class A

EMS:

EEN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5,
EN61000-4-6, EN61000-4-8, EN61000-4-11

Safety: UL, cUL, CE/EN60950

Shock: IEC60068-2-27

Vibration: IEC60068-2-6

Free Fall: IEC60068-2-32

Class 1 DIV 2: Pending*

DNV: Pending *

Environmental: WEEE, RoHS

MTBF: 325,000 hrs based on Mil-Hdbk-217F, GB

Warranty: 5 years

Management Specifications

Redundancy:

STP, RSTP
Dual Homing, Ring Coupling
X-Ring with recovery time < 300ms

Management Protocols:

SNMP v1/v2c, SMTP, Sntp, IGMP v1/v2 & Query mode, DHCP/Client, TFTP

MIB: MIB-II, Bridge MIB, Ethernet like MIB, VLAN MIB, Private MIB

Configuration:

Web interface management
Default button is available to restore default settings

VLAN:

Port Based VLAN
IEEE 802.1Q Tag VLAN (256 entries)
VLAN ID (Up to 4K, VLAN ID can be assigned from 1 to 4096.)
GVRP (256 Groups)*
Double Tag VLAN (Q in Q)*
Private VLAN*

Quality of Service:

The quality of service determined by port,
Tag and IPv4 Type of service,
IPv4/IPv6 Different Service*

Port Mirroring: Support 3 mirroring types: "RX, TX and Both packet"

IP Security:

Support 10 IP address accounts for system management security for Web, SNMP and Telnet management security to prevent intruder.

IGMP Snooping: v1 and v2, query mode, multicast group with 256 entries

Class of Service: Support IEEE802.1p class of service,
per port provides 4 priority queues

System Log: Support System log record and remote system log server

SNMP Trap: Up to 3 Trap stations

Cold start, Port link up, Port link down, Authentication Failure,
Private Trap for power status, Port Alarm configuration,
Fault alarm, X-Ring topology change

DNS: Provide DNS client feature and support Primary and Secondary DNS server

SMTP: Support SMTP Server and 6 e-mail accounts for receiving event alert

SNTP: Support SNTP to synchronize system clock in Internet