



FWI-701

Features

High Performance Network Switching Technology

- ✓ Wireless LAN IEEE 802.11 b/g compliant
- ✓ Compliant with IEEE 802.3, IEEE 802.3u, IEEE 802.11b, IEEE 802.11g
- ✓ Supports radio modules 2.412-2.472 GHz
- ✓ Supports Super G to transmit data rate up to 108 Mbps
- ✓ Supports point to point and point to multi-point bridging function
- ✓ Flexible four operating modes: Access Point, Bridge, AP Client and Repeater
- ✓ Strong Network Security with 64/128/152-bit WEP encryption and WPA function
- ✓ Supports DFS/TPC (Dynamic Frequency Selection and Transmit Power Control)
- ✓ Flexible Software configuration through WEB GUI interface for easy management

Robust Industrial Design

- ✓ Robust Weatherproof IP-67 housing protection

Reliable Power Design

- ✓ Supports Power Over Ethernet Design
- ✓ Supports power input of 12 VDC



Overview

The Falcon series FWI-701 is a 2.4 GHz IEEE 802.11 b/g compliant Wireless Outdoor Access Point available for Industrial Ethernet applications. With innovative technology design, FWI-701 provides 180 Mbps (Super G mode) high data rate for outdoor environment. It links two or more separate networks to create a single expanded LAN network cost effectively and efficiently. The robust IP-67 housing protects the device from harsh outdoor environment – weatherproof, waterproof, dustproof. A built-in 12 dBi panel antenna is included for flexibility in installation. FWI-701 supports four different operation modes namely Access Point, Bridge, AP Client and Repeater. In addition, the built-in Power over Ethernet design reduces the cost of power cables installation and provides future proof investment. To secure information, it comes with WEP encryption and WPA function. With of these advanced features, FWI-701 is a powerful Outdoor CPE solution produced for Industrial applications.

Hardware Specifications

Interface

Antenna Type: Integrated 12 dBi flat panel antenna

Access Point Interface:

Auto sensing MDI/MDI-X Ethernet 10/100Base-TX: RJ-45

Flash: 2 MB

SDRAM: 8 MB

Power Requirements

Power Input: DC 12V ± 5%, 1.5A(Max), Supply by PoE ,
PoE injector support AC100-240V

Output power: 100 mW

Power consumption: stand-by: 2.76 watts / Transmit: 3.60 watts

Physical

Dimensions: IP-67 standard, 106 mm (W) x 186 mm (H) x 61 mm (D)

Weight: 2.11 kgs

Installation: Pole mount or desktop

Accessories: Cables + Bracket + Power over Ethernet adapter

Environmental

Operating Temp: -10 to 70°C (14 to 158°F)

Storage Temp: -40 to 85°C (14 to 158°F)

Operating Humidity: 5%-90% RH (Non-condensing)

Technology Specifications

Operating Type:

AP/Bridge/Wireless Client/Repeater

Standard:

IEEE 802.11b/g ; IEEE 802.3 ; IEEE 802.3u

Radio Frequency Type:

DSSS (Direct Sequence Spread Spectrum)
OFDM (Orthogonal Frequency Division Multiplexing)

Modulation:

IEEE 802.11b: CCK, DQPSK, DBPSK
IEEE 802.11g: OFDM with BPSK, QPSK,
16QAM, 64QAM

Frequency Band:

America/FCC: 2.412-2.462 GHz (11 channels)
Europe CE/ETSI: 2.412-2.472 GHz (13 channels)

Transmission Power: 802.11b/g: 20dBm

Transmission Rate:

IEEE802.11b: 1/2/5.5/11 Mbps
IEEE 802.11g: 6/9/12/18/24/36/48/54/108 Mbps(Super G)

Data Rate:

Super G: Up to 108 Mbps
802.11g: Up to 54 Mbps
802.11b: Up to 11 Mbps

Sensitivity:

-86dBm @ 11 Mbps, PER< 8%; -64dBm @ 54 Mbps, PER< 10%

Regulatory Approvals

Safety: CE / EN60950-1

EMI: FCC Part 15

EMC: EN301 489-1, EN301 489-17

Radio: EN300 328

Wi-Fi compliant: YES

Shock: IEC60068-2-27

Vibration: IEC60068-2-6

Free Fall: IEC60068-2-32

Class 1 DIV 2: Pending *

DNV: Pending *

Environmental: WEEE, RoHS

MTBF: 425,000 hrs based on Mil-Hdbk-217F, GB

Warranty: 5 years

Management Specifications

Software:

Site Survey
DHCP Client
Suppressed SSID
Wireless access control by MAC address
(deny or accept)

WPA Support (WPA personal and enterprise)
Web-based configuration via popular browser
(MS IE, Netscape ...)

Windows "Locator" program to help find IP
in DHCP client mode
Firmware upgrade and configuration backup via Web
Reset to default by Web-UI
Supports SNMP v1/v2c

Security:

64/128/152-bit WEP encryption
Wi-Fi protected Access (WPA)